



Integrity ☐ ***Service*** ☐ ***Excellence***

Bio-Inspired Odor Source Localization

SOAR2 Review

12-15 JULY 2011

Adam J Rutkowski, Ph.D.

Research Engineer

AFRL/RWGIA


Air Force Research Laboratory

Report Documentation Page				Form Approved OMB No. 0704-0188	
Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.					
1. REPORT DATE JUL 2011		2. REPORT TYPE N/A		3. DATES COVERED -	
4. TITLE AND SUBTITLE Bio-Inspired Odor Source Localization				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S)				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Air Force Research Laboratory				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release, distribution unlimited					
13. SUPPLEMENTARY NOTES See also ADM202973. BioMav SOAR 2. Held at Chilworth Manor, United Kingdom on July 12-15, 2011. Supporting documents are attached to the report as separate files (WMV; AVI)., The original document contains color images.					
14. ABSTRACT					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT SAR	18. NUMBER OF PAGES 34	19a. NAME OF RESPONSIBLE PERSON
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified			



Why study odor tracking?

- Engineer odor tracking systems
 - Gas leaks
 - Hazardous waste
 - Explosive devices
 - Biological principles
- Understand biological principles
 - Mate/food finding
 - Pest population control
 - Engineered odor tracking systems



Manduca sexta




Odor tracking overview




- Odor plume properties
 - carried by wind
 - invisible
 - turbulent
 - artificial: hazardous waste, explosives
 - natural: pheromone, food
- Tracking agents
 - engineered: UAVs, UGVs, AUVs
 - natural: moths, cockroaches, fish

no strong gradient








Moth Odor Tracking Studies






Traditional 2D Analysis





- Odor-modulated anemotaxis
 - Move upwind (surge) when odor detected, move downwind (cast) when odor lost
 - Combination of straight legs and turns (zigzagging)
 - Turning controlled by a timing mechanism (interturn duration of 580 ms)
- Odor plume altitude is maintained



3D Analysis



- Counter-turns vertically with average ITD of 550 ms (90-95% of horizontal ITD)
- Vertical track width 75% of horizontal track width
- Temporal relationship between vertical and horizontal turns is unpredictable
- Turns are ambiguous (in both y and z)





Rutkowski, Quinn, and Willis
J Comp Phys A, 2009




3D Analysis

Downwind View of Moth Track



- Turns continuously as viewed from downwind
- Turn rate varies
- Turn direction varies



Rutkowski, Quinn, and Willis
J Comp Phys A, 2009




Bio-Inspired Odor Tracking Strategy



Instead of using inter-turn timers to control horizontal and vertical turning behaviors...

- Motion decomposed into normal (\mathbf{v}_n) and tangential (\mathbf{v}_t) components relative to wind
- Turn rate of \mathbf{v}_n $\psi = d\theta/dt$ depends on odor concentration
- Magnitude of \mathbf{v}_t depends on odor concentration



Rutkowski, Quinn, and Willis
ICRA, 2007




Bio-Inspired Odor Tracking Strategy



1. Measure odor concentration

Two linearly responding odor detectors



Rutkowski, Quinn, and Willis
ICRA, 2007




Bio-Inspired Odor Tracking Strategy

1. Measure odor concentration
2. Determine wind direction (not trivial)
3. Estimate odor plume centerline
Average of antenna position (in wind-normal plane) weighted by concentration and a “forgetting factor”

$$\hat{y}_s(t) = \frac{\alpha_{decy} c_{sur}(t-1) (\hat{y}_s(t-1) - \hat{v}_y(t) \Delta t)}{c_{sur}(t)}$$

$$\hat{z}_s(t) = \frac{\alpha_{decy} c_{sur}(t-1) (\hat{z}_s(t-1) - \hat{v}_z(t) \Delta t) + \epsilon_{right}(t) z_{right}(t) + \epsilon_{left}(t) z_{left}(t)}{c_{sur}(t)}$$

$$c_{sur}(t) = \alpha_{decy} c_{sur}(t-1) + \epsilon_{right}(t) + \epsilon_{left}(t)$$



Rutkowski, Quinn, and Willis
ICRA, 2007



Bio-Inspired Odor Tracking Strategy



1. Measure odor concentration
2. Determine wind direction
3. Estimate odor plume centerline
4. Calculate desired turn rate $\psi = d\theta/dt$

$$c = (c_{\text{right}} + c_{\text{left}}) / 2$$

Turn sharply (6 rad/s) if $c < c_{\text{threshold}}$


Turn as linear function of concentration if

$$c_{\text{threshold}} < c < c_{\text{saturation}}$$

Turn softly (1 rad/s) if $c > c_{\text{saturation}}$

Turn toward estimated source location

$$\text{sign}(\psi) = \text{sign}(\theta_s)$$



Rutkowski, Quinn, and Willis
ICRA, 2007




Bio-Inspired Odor Tracking Strategy



1. Measure odor concentration
2. Determine wind direction
3. Estimate odor plume centerline
4. Calculate desired turn rate
5. Calculate desired normal velocity

$$v_n = 30 \text{ cm/s}$$

$$\theta = \int \psi \, dt$$



Rutkowski, Quinn, and Willis
ICRA, 2007




Bio-Inspired Odor Tracking Strategy



1. Measure odor concentration
2. Determine wind direction
3. Estimate odor plume centerline
4. Calculate desired turn rate
5. Calculate desired normal velocity
6. Calculate desired tangential velocity (\mathbf{v}_t)

Surge upwind (30 cm/s) if $c > c_{\text{threshold}}$

Cast slowly downwind (7 cm/s) if $c < c_{\text{threshold}}$




Rutkowski, Quinn, and Willis
ICRA, 2007






Real vs. Simulated

Real




Simulated





Results

What if odor tracking continues after reaching source?





Tracker remains in vicinity of source!





Results

colored dots – tracker position
big black dot - estimated plume centerline





Results



casting and surging

counter-turns without inter-turn timer

"ambiguous" turns




That's great, but how are wind velocity
and self-motion velocity estimated?



Insect Navigation System

- no GPS
- no dedicated accelerometer
- eyes
 - not distance estimators
 - too close together
 - fixed focus
 - small region of overlap
 - optic flow
- head hairs and antennae
 - speed **and direction** of air-current





Egomotion and Wind Velocity Estimation



unique values for


- height (h)
- groundspeed (\mathbf{v}_g)
- wind velocity (\mathbf{w})

cannot be determined from
single measurements of

- air-current velocity (\mathbf{v}_a)
- optical flow (λ)

However...

height **can** be estimated by assuming
wind is smooth over short time
period (~ 1 s)












Egomotion and Wind Velocity Estimation

Moth flight track recorded at 30 Hz




Wind data from open field recorded at 30 Hz



Simulated airspeed data : $\mathbf{v}_a = (\mathbf{v}_g - \mathbf{w}) + \eta_a$

Simulated optical flow data : $\lambda = (\mathbf{v}_g / h) + \eta_\lambda$




simulated
sensor noise

optical flow: 30 Hz, $\sigma=0.2$ rad/s
airspeed: 30 Hz, $\sigma=100$ mm/s



Height Estimation Results Using Aero/Optical Fusion



$m=2, n=50$

$$\epsilon_n = \hat{h} - h$$

$$\text{mean}(\epsilon_n) = -0.12 \text{ mm}$$

$$\text{std}(\epsilon_n) = 22 \text{ mm}$$

Quality of velocity estimation depends on quality of height estimation







Ground speed Estimation Results Using Aero/Optical Fusion






Ground speed (\mathbf{v}_g) estimate lags by two timesteps

Lag caused by finite difference approximation of velocity from optical flow

	v_{gx} (mm/s)	v_{gy} (mm/s)	v_{gz} (mm/s)
			
	11	0	5
	10	3	6
	140	144	162
	28	27	28

Rutkowski, Miller, Quinn, and Willis
Biol Cybern, 2011












Wind Estimation Results Using Aero/Optical Fusion

Wind estimate also obtained

Lag also present, but minimal compared to noise

	w_x (mm/s)	w_y (mm/s)	w_z (mm/s)
	12	3	5
	10	3	5
	76	61	68
	64	60	60

Rutkowski, Miller, Quinn, and Willis
Biol Cybern, 2011







Odor Tracking and Aero/Optical Fusion



- Fusion of vision and airspeed makes odor tracking possible
- Height estimation fails with constant velocity motion



- Motion excitation, as produced by the odor tracking task, allows for state observability






Summary



- Moth odor tracking behavior in 3D is NOT a simple extension of 2D ideas
- Moth-like “counter-turning” behavior can be achieved without inter-turn timers
- State and wind estimation can be performed using insect sensory system
- A “drunken stumble” can actually be beneficial



Thank you for your attention!




Additional Slides




Odor Plume Model

- Normally distributed odor concentration
- Plume narrows with approach to odor source
- Centerline concentration increases with approach to odor source



Zannetti

But remember... odor plume is patchy







Odor Plume/Sensor Model




Odor concentration at a single location



Odor concentration at a single timestep




Time-averaged odor concentration



Randomness simulates turbulence


Normally distributed concentration profile






Odor plume narrows with approach to the source



Results






controls
upwind velocity
turn rate
as function of
odor concentration





Spiraling Results



Turns in the direction of the estimated odor source location